

## CARTER

### 203BB-03 S3S SC FO LG SR ESD

STANDARD EN ISO 20345:2022+A1:2024  
SIZES 37-47



Three-dimensional **SPYDER-NET**: lining with moisture absorption and release properties. Its special three-dimensional structure provides exceptional shape memory and high snag-resistance

Reflective material

Dual density **ICON PU/PU** sole designed to offer maximum comfort, slip resistance, excellent performances across all terrains, from wet to dry conditions. It has been tested in SATRA laboratories to resist slipping on metal grates (Kennedy Grating Test) and wooden boards (Scaffold Board Test)



#### Dual density ICON PU/PU

- Resistant to hydrocarbons
- Antistatic sole (A)
- Non-slip sole suitable for use on metal and wooden grates - SATRA Tests
- Self-cleaning profile to ensure maximum ground grip
- Wide fit for maximum stability and protection
- Shock-absorbing heel




**BOA® Fit System**: an adjustable micro-dial, ultra-strong lightweight laces and a low-friction lace guide. Designed for easy, precise and secure adjustment

**IDROTECH** fullgrain leather upper, resistant to water penetration and absorption

	A - Antistatic
	P - Anti-perforation insert
	E - Energy absorption in the heel region
	FO - Sole resistant to hydrocarbons
	Toecap resistant up to an impact of 200 joules and crushing of 15 KN
	SC - abrasion resistant overcap
	WPA - Upper resistant to water penetration and absorption
	LG - ladder grip system
	SR - Slip resistance on ceramic tile with glycerin

Esolight 1.0 polyurethane midsole. The low-density polyurethane microcells enhance energy absorption ensuring comfort and lightness

**PZX** fiberglass toe cap and **TXZERO STRONG** anti puncture insole made of high tenacity fibers to obtain a flexible textile that adapts to the movement of the foot; it is intrinsically antistatic



T-01

- Anatomical insole for increased comfort
- High-density foam = energy absorption and rebound
- Lining made from conductive micro-perforated fabric to reduce wear and tear